

Bande wallwasher Low-Voltage Track




- White
● Black

Features




Dimensions

6W



12W



Electrical system

Total power consumption:	6W/12W
Power input:	48V
Operating temperature:	-10°C ~ 35°C
Dimming option:	0-10V / Dali / Casambi
Insulation class:	Class III

Light source

LED type:	SMD
CCT:	2700K/3000K/4000K
CRI:	Ra>92
Beam angle:	30°
UGR:	<19

Housing

Lamp body diameter:	19mm x 108mm (6W)/19mm x 216.4mm (12W)
Material:	Aluminum
Weight:	320g/545g

Warranty

Period:	5-year warranty
----------------	-----------------

Lumen output

Angle \ CCT	2700K	3000K	4000K
30°(6W)	432lm	480lm	514lm
30°(12W)	720lm	800lm	805lm

Nomenclature

*Applicable model: M41906xx90xxxx (xx: dynamic codes)

Product Code	System Power	CCT	CRI	Beam Angle	Driver/Control	Serial No.
M419	06(6W)	27(2700K)	90(90)	30(30°)	N(Non-Dim)	01(Black)
	12(12W)	30(3000K)			A(0-10V dim)	02(White)
		40(4000K)			D(DT6)	

Illuminance distance data

Bande wallwasher

6W



30°

h(m)	E(lx)	Ø (m)	S_B(sq.m)
1	2042.70	0.44	0.2
2	510.67	0.88	0.6
3	226.97	1.32	1.4
4	127.67	1.76	2.5
5	81.71	2.20	3.9

Bande wallwasher

12W



30°

h(m)	E(lx)	Ø (m)	S_B(sq.m)
1	3951.61	0.44	0.2
2	987.90	0.89	0.6
3	439.07	1.33	1.4
4	246.98	1.77	2.5
5	158.06	2.21	3.9