

RoboFocus





Motorised 3-phase track lighting. Integrated power supply.

- White
● Black

Features



Dimensions



Tolerance: ±2mm

Electrical system

Total power consumption:	15W
Power input:	120–277Vac, 50/60Hz
Operating temperature:	–10°C ~ 35°C
Power factor:	>0.95
Insulation class:	Class II
Motor type:	Stepping motor
Control protocol:	DMX / 2.4G Remote control

Light source

LED type:	COB
CCT:	2700K/3000K/4000K/Tunable White(2700K– 5700K)
CRI:	Ra>90, R9>50
Beam angle:	15° / 24° / 30° / 45°

Housing

Lamp body diameter:	63mm
Material:	Aluminum, plastic
Weight:	2.1kg

Warranty

Period:	5-year warranty
----------------	-----------------

Lumen output

Angle \ CCT	2700K	3000K	4000K	2700K–5700K
15°	900lm	1035lm	1175lm	785lm–910lm
24°	810lm	945lm	1075lm	725lm–840lm
30°	860lm	990lm	1125lm	755lm–865lm
45°	745lm	860lm	980lm	650lm–755lm

Accessory



Beam filter	Order No.
24°	2A13
30°	2A14
45°	2A15

Nomenclature

*Applicable model: TLRF15xx90xxxx (xx: dynamic codes)

Type	Series Name	System Power	CCT	CRI	Beam Angle	Driver/Control	Serial No.
TL	RF(RoboFocus)	15(15W)	27(2700K)	90(90)	15(15°)	D(DMX)	01(Black)
			30(3000K)		24(24°)	6(2.4 GHz)	02(White)
			40(4000K)		30(30°)		
					45(45°)		